Safety Data Sheet

Spraylite Series I & 100 & 400 Series of Series II and III

MSDS No. 9780.10

Date of Preparation: 7/16/96 Revision 8/12/13

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Spraylite Series I & 100 & 400 Series of Series II and III

General Use: Filler or extender

Manufacturer: The R. J. Marshall Company

26776 W. 12 Mile Road Southfield, MI 48034-7807

Phone: (248) 353-4100, Fax: (248) 948-6460

Emergency Phone: (800) 424-9300

Date Revised: 8/12/13 **Preparer:** Stephanie Nichols

R 0 PPE^{† E} TSec. 8

F

HMIS H

0

Section 2 - Hazards Identification

Potential Health Effects



Warning:

Hazard Statements:

S20/21: When using do not eat, drink, or smoke.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of water.

Precautionary Statements:

S8: Keep container dry

S36/27/39: Wear suitble protective clothing, gloves, and eye/face protection. S43: In case of fire use water spray, carbon dioxide, or other dry chemical.

R36/37/38: Irritating to eyes, respiratory system, and skin.

Primary Entry Routes: Inhalation, Eye, and Ingestion.

Acute Effects

Inhalation: Inhalation of high concentrations of this inert nuisance particulate can result in mild irritation of the respiratory

Eye: May cause irritation through mechanical abrasion. **Skin:** May cause irritation through mechanical abrasion.

Ingestion: Unlikely.

Section 3 - Composition / Information on Ingredients

Ingredient Name	CAS Number	Percentage
Crystalline Silica	14808-60-7	0.5% max
Inorganic Filler		100% max

Section 4 - First Aid Measures

Inhalation: If overcome by high dust concentrations, remove to a ventilated area.

Eye Contact: Flush eyes thoroughly for 15 minutes taking care to rinse under eyelids. Do not scrub. Abrasion may cause

irritation. If discomfort continues, continue to wash with water. If irritation persists, consult a physician.

Skin Contact: Wash skin thoroughly with soap and water for at least 15 minutes. Consult a physician if irritation persists. **Ingestion:** Ingestion of very large quantities may result in intestinal obstruction and/or constipation. Considered to be of very low toxicity.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: n/a

Special Precautions/Procedures: n/a

revision_date 8/12/13 Spraylite Series I, 100 & 400 Series of Series II and III MSDS No. 9780.10

Section 5 - Fire-Fighting Measures

Flash Point: None known.
Flash Point Method: n/a
Burning Rate: Not determined.

Auto-ignition Temperature: Not determined. **Flammability Classification:** Non-flammable.

Extinguishing Media: S43: In case of fire use water spray, carbon dioxide, or other dry chemical.

Unusual Fire or Explosion Hazards: None known.

Hazardous Combustion Products: None.

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing

apparatus (SCBA) with a full face-piece operated in pressure-demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Collect solids. Recycle if possible.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Avoid generating dust during handling.

Storage Requirements: S8: Keep material dry.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

Protective Clothing/Equipment: S36/37/39: Wear suitable protective clothing, gloves, and eye/face protection.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: S20/21: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

	OSHA PEL		ACGIH TLV	
Ingredient	TWA	STEL	TWA	STEL
Inorganic Filler	15 mg/m ³ total 5 mg/m ³ respirable	none estab.	10 mg/m ³	none estab.
Crystalline Silica	10 mg/m ³ respirable dust	none estab.	0.025 mg/m ³ respirable dust	none estab.

Section 9 - Physical and Chemical Properties

Physical State: powder

Appearance and Odor: off-white odorless powder

Odor Threshold: n/e Vapor Pressure: n/e Vapor Density (Air=1): n/a Formula Weight: n/a

Specific Gravity (H₂O=1, at $4 \,^{\circ}$ C): 0.6-1.3

pH: n/e Viscosity: n/a Refractive Index: n/a Surface Tension: n/a

Density: n/e

Water Solubility: Slight Other Solubilities: n/a Boiling Point: n/a

Freezing/Melting Point: n/a

% Volatile: n/a Evaporation Rate: n/a Flash Point: None known. Flash Point Method: n/a Burning Rate: Not determined.

Auto-ignition Temperature: Not determined. **Flammability Classification:** Non-flammable.

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Calcium Carbonate will react with strong acids to form carbon dioxide.

Conditions to Avoid: None known. **Hazardous Decomposition Products:** n/a

Section 11- Toxicological Information

Toxicity Data:*

Eye Effects: Nuisance dust. May cause irritation through mechanical abrasion. Flush with water for at least 15 minutes. Consult physician if irritation is persistent.

Skin Effects: Nuisance dust. May cause irritation through mechanical abrasion. Wash skin thoroughly with soap and water.

Acute Inhalation Effects: Nuisance dust. Overexposure to dust may cause irritation to the respiratory tract. Should this occur, remove affected individual to fresh air. If symptoms persist, consult a physician.

Acute Oral Effects: None known.

Carcinogenicity: IARC has listed crystalline silica as a human

carcinogen.

Chronic Effects: This product contains crystalline silica as an impurity. Prolonged exposure to respirable crystalline silica dust concentrations exceeding occupational exposure limits without the use of the proper respirator may increase the risk of developing disabling lung diseases called silicosis. This product is not listed as a carcinogen by OSHA, NTP, or IARC.

Section 12 - Ecological Information

No information available.

Section 13 - Disposal Considerations

Disposal: Recycle or landfill if possible. This substance is inert and does not require special disposal methods. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101): This product is not classified as dangerous under the transport regulations for road, rail, sea, or air transport.

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261.??): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) Not listed

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed

Crystalline Silica is subject to the reporting requirements of California's Safe Drinking Water and Toxic Enforcement Act of 1986 ("Proposition 65").

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

TSCA

This substance or all of its components are on the Chemical Substances Inventory of the Toxic Substance Control Act (TSCA Inventory [USA]). Please note that this product is not subject to any legal reporting requirements under these acts.

revision_date 8/12/13 Spraylite Series I, 100 & 400 Series of Series II and III MSDS No. 9780.10

INTERNATIONAL REGULATIONS

Canadian Domestic Substances List: Components of this product are listed on the Canadian DSL.

European Community: Components of this product are listed on EINECS, European Inventory of Existing Commercial

Chemical Substances.

Australia: Components of this product are listed on AICS, Australia Inventory of Chemical Substances.

China: Components of this product are listed.

Japan: Components of this product are listed on ENCS, Japan Existing and New Chemical Substances.

Korea: Components of this product are listed on Existing and Evaluated Chemical Substances.

Philippines: Components of this product are listed on PICCS, Philippines Inventory of Chemicals and Chemical Substances.

Section 16 - Other Information

Prepared By: Stephanie Nichols

Revision Notes: converted to SDS, added SL425

Product Grades Available from the R. J. Marshall Company (this list may be incomplete):

Spraylite 101	Spraylite 131	Spraylite 403	Spraylite 420	Spraylite 545
Spraylite 110	Spraylite 132	Spraylite 403A	Spraylite 421	
Spraylite 110A	Spraylite 133	Spraylite 404	Spraylite 425	
Spraylite 110V	Spraylite 201	Spraylite 405	Spraylite 430	
Spraylite 120	Spraylite 301	Spraylite 410	Spraylite 430A	
Spraylite 121	Spraylite 401	Spraylite 410A	Spraylite 431	
Spraylite 130	Spraylite 402	Spraylite 410V	Spraylite 501	

Disclaimer: Information contained herein is presented in good faith and is based on data believed to be accurate. However no warranty is expressed or implied regarding this information or the results obtained from the use of this Material Safety Data Sheet, whether it originates with The R. J. Marshall Company or others. This Safety Data Sheet relates only to the specific material designated herein. It does not relate to use with other material or processes. This information is supplied with the condition that the user will make appropriate determination as to its suitability for their purpose prior to using it.