



Marshall Additive
TECHNOLOGIES
DIVISION OF THE R. J. MARSHALL COMPANY

26776 W. 12 Mile Road
Southfield, MI 48034
248-353-4100 phone
248-948-6460 fax
800-338-7900 toll free
888-514-8600 customer care
www.rjmarshall.com

C-TEC™ SD200 Flame & Smoke Reduction

Typical Physical Properties:

Free Moisture	0.5% Max
+325 mesh	0.2% Max
Median Particle Size	4um
Specific Gravity	3.37

Potential Antimony Oxide replacement.

APPLICATIONS:

C-TEC SD200 is a flame- and smoke-suppressant additive designed to replace the customary level of antimony oxide, while maintaining flame-retardancy but with substantially lower cost, and lower smoke in PVC and other chlorine-containing polymers. C-TEC SD200 has been found to be beneficial in low temperature applications and hinders embrittlement.

PACKAGING: 50 lb. bags, pallet weight 2500 lbs.

Terms and Conditions of Sale: All statements, technical information and recommendations are based on tests we believe to be reliable, the accuracy or completeness is not guaranteed, and the following is made in place of all warranties, expressed or implied. Our only obligation is to replace product proved to be defective. We shall not be liable for any injury, loss or damage, direct or indirect, from using or not being able to use the product. Before using, customer must determine the suitability of the product for the intended use and customer assumes the responsibility. This statement may not be changed except by an agreement signed by an officer of The R.J. Marshall Company.

December 2016