Safety Data Sheet

Alumina Trihydrate

Date of Preparation: 12/10/96

Section 1 - Chemical Product and Company Identification

	drate, ATH, Aluminum ydrate, hydrated alumi material, abrasive, fire	h Hydroxide, Trihydrat na, Trioxyde d'alumin	um, Aluminum Tri uppressant for plast	hydroxide, Al ₂ 0 ₃ · 3H ₂ C tics, ceramic material. e: (800) 424-9300 30/17	
Phone (2	248) 353-4100, Fax (24	18) 948-6460	- •		
	Section 2	- Hazards Iden	tification		HMIS
Classification of the sub Classification according Classification according	stance or mixture: to Regulation (EC) No	o 1272/2008 (CLP): N	lot classified	ied	$\begin{array}{c c} \mathbf{H} & 0 \\ \mathbf{F} & 0 \\ \mathbf{R} & 0 \\ \mathbf{PPE}^{\dagger E} \\ ^{\dagger}Sec. 8 \end{array}$
Hazard Pictogram: Non Hazard Statements: No Precautionary Statemen Other hazards: None	one				5ec. 8
	Section 3 - Con	nposition / Info	rmation on I	ngredients	
Ingredient Name	CAS Number	EC Number	Weight	H phrases	R phrases
Alumina Trihydrate	21645-51-2	244-492-7	100%	None	None
irritation. If discomfort Skin Contact: Wash skin Ingestion: If swallowed, Most important sympto Indication of any immed	n thoroughly with soap dilute with large amou ms and effects, both a	and water. Consult a nts of water. Seek me	physician if irritatio dical advice. one		
		n and special freather		28	
Suitable Extinguishing I Unsuitable Extinguishin Special hazards arising Hazardous Combustion Fire-Fighting Instructio	Media: Use extinguish ng Media: None from the chemical: N Products: None.	ing measures appropri			
	Section	6 - Accidental F	Release Meas	ures	
Personal precautions, proventilation wear respirat Environmental precaution Methods and materials	tory protection.				-
		-	rr		gulations.
	Secti	on 7 - Handling		е	gulations.

MSDS No. 9605.50

Revision: 6/30/17

Alumina Trihydrate

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Eye Protection: Wear tightly fitting safety goggles or safety glasses with side shields.

Hand Protection: Protective gloves are recommended.

Glove material: Nitril rubber **Layer thickness:** 0.11 mm **Breakthrough time:** >480 min

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

	OSHA PEL	ACGIH TLV		
Ingredient	TWA	STEL	TWA	STEL
Alumina Trihydrate	none estab.	none estab.	none estab.	none estab.
Nuisance Dust	15 mg/m ³ total, 5 mg/m ³ respirable	none estab.	none estab.	none estab.

Section 9 - Physical and Chemical Properties

Physical State: white powder Vapor Pressure: n/e Appearance and Odor: white odorless powder Vapor Density (Air=1): n/a Odor Threshold: n/e **Relative Density: 2.42 pH:** 8-9 (20% solution) Water Solubility: Insoluble Freezing/Melting Point: Decomposes before melting. Other Solubilities: Soluble in alkaline aqueous solutions or in HCL, H2SO4, and other strong acids in the presence of **Boiling Point:** n/a Flash Point: Not applicable. some water. Flash Point Method: Not flammable. **Partition coefficient: n-octanol/water:** not applicable Evaporation Rate: n/a Auto-ignition Temperature: Does not ignite. Flammability: Not flammable. **Decomposition temperature:** >200C Upper/lower flammability or explosive limits: n/a Viscosity: n/a

Section 10 - Stability and Reactivity

Reactivity: None known.

Chemical stability: Alumina trihydrate is stable at room temperature in closed containers under normal storage and handling conditions.

Possibility of hazardous reactions: No hazardous reactions known.

Conditions to avoid: Temperature >392°F (200°C).

Incompatible materials: Strong acids and bases. Alumina trihydrate reacts vigorously with strong acids and will dissolve in caustic solutions.

Hazardous decomposition products: n/a

Alumina Trihydrate

Section 11- Toxicological Information

Toxicity Data:*

Information on toxicological effects:

Acute:

cute:						
	Value	Species	Туре	Test Substance		
Oral	>2000 mg/kg bw	Rat	Acute	Aluminum		
				hydroxide		
Dermal	Not applicable					
Inhalation	LC ₅₀ : 7.6 mg/l	Rat	Acute	Analogue		
Skin Corrosion	Not corrosive	Rabbit	Acute	Analogue		
Skin Irritation	Not irritating	Rabbit	Acute	Analogue		
Eye Irritation	Not irritating	Rabbit	Acute	Analogue		
Sensitization	Non-sensitizing					

Repeated dose toxicity:

	Value	Species	Туре	Test Substance
Oral	NOAEL: 30 mg/kg	Rat	Chronic	Analogue
	bw/day			
Inhalation	NOAEL: 70 mg/m ³	Rat	Sub-chronic	Analogue

Carcinogenicity: No evidence of carcinogenic effects.

Mutagenicity: No evidence of any mutagenic effects.

Reproductive toxicity: No evidence of any reproductive toxicity effects.

Section 12 - Ecological Information

Eco-toxicity:

Fish toxicity: $LC_{50}>100 \text{ mg/l}$ in Salmo trutta. Invertebrate toxicity: $EC_{50}>100 \text{ mg/l}$ in Daphnia Magna Algae toxicity: $EC_{50}>100 \text{ mg/l}$ in Selenastrum capricornutum

Persistence and degradability: Not applicable for inorganic substances.

Bio-accumulative potential: Not applicable

Mobility in soil: Not applicable.

Results of PBT and vPvB assessment: This product does not meet the classification as PBT/vPvB.

Other adverse effects: None known.

Section 13 - Disposal Considerations

Disposal: Recycle if possible or landfill. This substance is inert and does not require special disposal methods. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101): This product is not classified as dangerous under the transport regulations for road, rail, sea, or air transport.

UN Number: not classified as dangerous goods UN proper shipping name: not classified as dangerous goods Transport hazard classes: None Packaging group: None Environmental hazards: None Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: No hazardous goods. Special precautions for user: None

Alumina Trihydrate

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33) RCRA Hazardous Waste Classification (40 CFR 261.??): Not classified CERCLA Hazardous Substance (40 CFR 302.4) not listed SARA Toxic Chemical (40 CFR 372.65): Not listed SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed SARA 311/312 Hazard: None

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed OSHA Specifically Regulated Substance (29CFR 1910.???)

Proposition 65: Not listed

Inventory Lists: This product is listed on the following inventory lists:

TSCA	Australia	Canada	China	Europe	Japan	Korea
	AICS	DSL	IECSC	EINECS	ENCS	ECL
Listed	Listed	Listed	Listed	244-492-7	1-17	KE-00980

New Zealand	Swiss	Philippines	Taiwan	Canada
NZIoC	Giftliste	PICCS	NECI	WHMIS
Listed	G-4621	Listed	Listed	Not listed

International Regulations:

Regulation (EC) No 2037/2000 (Ozone Depleting Substances); Not applicable

Regulation (EC) No 850/2004 (Persistent Organic Pollutants): Not applicable

Regulation (EC) No 689/2008 (Export and Import of Dangerous Substances): Not applicable

Directive 2002/95/EC (RoHS): Not applicable

Directive 2002/96/EC (WEEE): Not applicable

Directive 1999/13/EC (VOC): Not applicable

Restrictions according to TITLE VIII of the Regulation (EC) No 1907/2006 (REACH): None

S-phrases:

S8: Keep container dry.

S36/37/39: Wear suitable protective clothing, gloves, and eye protection.

WEEE: Waste Electrical and Electronic Equipment

VOC: Volatile Organic Compounds

RoHS: Restriction of Hazardous Substances

Section 16 - Other Information

Prepared By: Stephanie Nichols

Revision Notes: updated throughout

Product Grades Available from the R. J. Marshall Company (this list may be incomplete):

OFI	A202 (A,W)	AH170(A,C,V)	DGXW1
OFIII	A203H	AH190	DGXW2
OFV	A204(A,W)	AH255(A,W)	EM107
OFVS	A205(A)	AH270(A,C,V, W)	EXT DF 168
OFVI	A206(A,H,W)	AH280(A,C,V,W)	ATH-A
OF7	A208(A)	AH285W	ATH-B
OF136	A210(A)	AH290(A,C,V,W)	DT1080
OF250	A210SP	AH290S	KX-1
OF255A	A212(A)	AH298(A,C)	DT1186
OF300	A245(W)	AH330(A,C,V,W)	STM1410
OF500	A236HL	AH331(A)	AC470AN
OF505	A200SB1	AH430(A,C,H,V,W)	AC480AN
OF600	RC802(A)	AH610	
		AH690	
OP50OC	A102	AH171(A)	
OR150	A104	AH271(A)	
OR250	A105	AH281(A)	
OR255A	A106	AH291(A)	
RC822	A108	AH331(A)	
A4555	A110	AH431(A)	
8515	A112	AH691	
HF136	A130	AF330(A)	
	A145		
MX100	A104A	MAXTOOL710	
MX104		MAXTOOL815	
MX200			
	OFIII OFV OFVS OFVI OF7 OF136 OF250 OF255A OF300 OF505 OF600 OP500C OR255A OF600 OP500C OR255A RC822 A4555 8515 HF136 MX100 MX104	OFIII A203H OFV A204(A,W) OFVS A205(A) OFVI A206(A,H,W) OF7 A208(A) OF7 A208(A) OF7 A208(A) OF36 A210(A) OF250 A210(A) OF250 A212(A) OF300 A245(W) OF500 A236HL OF505 A200SB1 OF600 RC802(A) OP500C A102 OR150 A104 OR255 A106 RC822 A108 A4555 A110 8515 A112 HF136 A130 A145 MX100 MX104 MX104	OFILI A203H AH190 OFV A204(A,W) AH255(A,W) OFVS A205(A) AH270(A,C,V,W) OFVI A206(A,H,W) AH280(A,C,V,W) OF7 A208(A) AH285W OF136 A210(A) AH290(A,C,V,W) OF250 A210(A) AH290(A,C,V,W) OF250 A210XP AH290S OF255A A212(A) AH298(A,C) OF300 A245(W) AH330(A,C,V,W) OF500 A236HL AH331(A) OF505 A200SB1 AH430(A,C,H,V,W) OF600 RC802(A) AH610 AH690 OP50OC OF150 A102 AH171(A) OR150 A104 AH271(A) OR255A A106 AH291(A) RC822 A108 AH331(A) A4555 A110 AH431(A) 8515 A112 AH691 HF136 A130 AF330(A) A145 MX100 A104A MAXTO

Note: This includes all EXP ATH blends.

Disclaimer: Information contained herein is presented in good faith and is based on data believed to be accurate. However no warranty is expressed or implied regarding this information or the results obtained from the use of this Safety Data Sheet, whether it originates with The R. J. Marshall Company or others. This Safety Data Sheet relates only to the specific material designated herein. It does not relate to use with other material or processes. This information is supplied with the condition that the user will make appropriate determination as to its suitability for their purpose prior to using it.