

Safety Data Sheet

Densified Granite Effect Series & Luxury Series Granite

MSDS No. 9623.19

Date of Preparation: 7/16/96

Revision: 6/6/13

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Densified Granite Effect, all colors

General Use: Used in solid surface applications

Manufacturer: The R. J. Marshall Company
26776 W. 12 Mile Road
Southfield, MI 48034-7807
(248) 353-4100

Emergency Phone: (800) 424-9300

Date Revised: 6/6/13

Prepared By: Stephanie Nichols

HMIS

H 1

F 0

R 0

PPE† E

†Sec. 8

Section 2 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Potential Health Effects

Warning: Irritant

Primary Entry Routes: Inhalation, Eye, and Ingestion

Acute Effects

Inhalation: Inhalation of high concentrations of this inert particulate can result in mild irritation of the respiratory tract.

Eye: May cause irritation through mechanical abrasion.

Skin: May cause irritation through mechanical abrasion.

Ingestion: Unlikely.

Carcinogenicity: IARC, OSHA, and NTP do not list this product or any of its components as a carcinogen.

Chronic Effects: n/a

Section 3 - Composition / Information on Ingredients

Ingredient Name	CAS Number
Alumina Trihydrate	21645-51-2
Filled Polyester	-----

Section 4 - First Aid Measures

Inhalation: If overcome by high dust concentrations, remove to a ventilated area. Seek medical attention for any symptoms that may develop.

Eye Contact: Flush eyes thoroughly for 15 minutes taking care to rinse under eyelids. Do not scrub. Abrasion may cause irritation. If discomfort continues, continue to wash with water. If irritation persists, consult a physician.

Skin Contact: Wash skin thoroughly with soap and water for at least 15 minutes. Consult a physician if irritation persists.

Ingestion: Consult a physician.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: n/a

Special Precautions/Procedures: n/a

Section 5 - Fire-Fighting Measures

Extinguishing Media: Water spray, carbon dioxide or other dry chemical.

Unusual Fire or Explosion Hazards: None known.

Hazardous Combustion Products: May include carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, and styrene.

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Collect solids. Recycle if possible.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Avoid generating dust during handling.

Storage Requirements: S8 Keep material dry.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Use dust mask if necessary.

Protective Clothing/Equipment: S36/37/39 Wear suitable protective clothing, gloves, and eye protection. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: S20/21 Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Trace Impurities:

Ingredient	OSHA TWA	PEL STEL	ACGIH TWA	TLV STEL
Alumina Trihydrate	none estab.	none estab.	None estab.	none estab.
Filled Polyester	none estab.	none estab.	None estab.	none estab.

Section 9 - Physical and Chemical Properties

Physical State: Powder

Appearance and Odor: odorless, color varies.

Odor Threshold: n/e

Vapor Pressure: n/a

Vapor Density (Air=1): n/a

Formula Weight: n/a

Density: n/e

Specific Gravity (H₂O=1, at 4 °C): 2.2-2.3

pH: n/e

Flash Point: n/a

Flash Point Method: n/a

Burning Rate: not determined.

Water Solubility: Slight.

Other Solubilities: n/a

Boiling Point: n/a

Freezing/Melting Point: n/a

Viscosity: n/a

Refractive Index: n/a

Surface Tension: n/a

% Volatile: n/a

Evaporation Rate: n/e

Autoignition Temperature: not determined

Flammability Classification: Non-flammable.

Section 10 - Stability and Reactivity

Stability: This material is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong alkaline may destroy surface appearance.

Conditions to Avoid: None known.

Hazardous Decomposition Products: Thermal oxidative decomposition of this material may produce carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, and styrene.

Section 11- Toxicological Information**Toxicity Data:***

Eye Effects: Nuisance dust. May cause irritation through mechanical abrasion. Flush with water for at least 15 minutes. Consult physician if irritation is persistent.

Acute Inhalation Effects: Overexposure to dust may cause irritation to the respiratory tract. Should this occur, remove affected individual to fresh air. If symptoms persist, consult a physician.

Skin Effects: Nuisance dust. May cause irritation through mechanical abrasion. Wash skin thoroughly with soap and water.

Acute Oral Effects: None known.

Chronic Effects: None known.

Carcinogenicity: Neither this product nor any of its components are listed as carcinogens by IARC, NTP, OSHA, or ACGIH.

Section 12 - Ecological Information

No information available.

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101): This product is not classified as dangerous under the transport regulation for road, rail, sea, or air transport.

Section 15 - Regulatory Information**EPA Regulations:**

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification: Not classified

CERCLA Hazardous Substance (40 CFR 302.4) not listed

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

TSCA

This substance or all of its components are on the Chemical Substances Inventory of the Toxic Substance Control Act (TSCA Inventory [USA]). Please note that this product is not subject to any legal reporting requirements under these acts.

INTERNATIONAL REGULATIONS

Canadian Domestic Substances List: Components of this product are listed on the Canadian DSL.

European Community: Components of this product are listed on ECHOIN, the European Core Inventory (EC) market.

Section 16 - Other Information

Prepared By: Stephanie Nichols

Revision Notes: updated to SDS format

Product Grades Available from the R. J. Marshall Company (this list may be incomplete):

DGE 200	DGE 622	LXS 355	LXX 629	DGE 330B	SPR 570
DGE 205	DGE 625	LXS 365	LXX 855	DGE 390B	SPR 670
DGE 209	DGE 725	LXS 370	LXX 903	DGE 622B	
DGE 210	DGE 750	LXS 450	LXX 904	LXX 202B	
DGE 300	DGE 800	LXS 630	LXX 905		
DGE 305	DGE 805	LXS 720	LXX 910	SPC 213	
DGE 307		LXS 850	LXX 911	SPC 214	
DGE 310	LXS 203		LXX 912	SPC 260	
DGE 320	LXS 206	LXX 202	LXX 204SE	SPC 324	
DGE 321	LXS 212	LXX 204	LXX 260SE	SPC 626	
DGE 330	LXS 230	LXX 260	LXX 302SE	SPC 807	
DGE 335	LXS 235	LXX 302	LXX 327SE	SPR 204	
DGE 340	LXS 315	LXX 327	LXX 357SE	SPR 250	
DGE 390	LXS 319	LXX 336	LXX 430SE	SPR 312	
DGE 400	LXS 320	LXX 357	LXX 435SE	SPR 331	
DGE 420	LXS 322	LXX 430	LXX 629SE	SPR 352	
DGE 620	LXS 345	LXX 435	LXX 855SE	SPR 430	

Note: This includes all EXP DGE blends and all DGE SB, DGE F, LXSSB, and GRN special blends.

Disclaimer: Information contained herein is presented in good faith and is based on data believed to be accurate. However no warranty is expressed or implied regarding this information or the results obtained from the use of this Material Safety Data Sheet, whether it originates with The R. J. Marshall Company or others. This Material Safety Data Sheet relates only to the specific material designated herein. It does not relate to use with other material or processes. This information is supplied with the condition that the use will make appropriate determination as to its suitability for their purpose prior to using it.