Safety Data Sheet

GruberCare Interphase Wax

Date of Preparation: 7/17/15 Revision: 7/17/15

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: GruberCare Interphase Wax

General Use: Wax

Manufacturer: Marshall-Gruber Company, LLC

A subsidiary of The R. J. Marshall Company

220 Airport Drive Mansfield, TX 76063

Phone: (682)422-9674, Fax: (682)518-9762

Emergency Phone: (800)424-9300

SDS No. 20008.00

Date Revised: 7/17/15 **Preparer:** Stephanie Nichols

Section 2 – Hazards Identification

Classification of the chemical in accordance with paragraph (d) of 1910.1200: Hazardous.

GHS Classifications:

Flammable Liquid Category 3 Germ Cell Mutagenicity Category 1B Carcinogenicity Category 1B Eye Irritant Category 2 STOT SE Category 3 Aspiration Toxicity Category 1

Signal words: Danger



Symbol:

Hazard statements:

H226: Flammable liquid

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

H340: May cause genetic defects.

H350: May cause cancer.

Precautionary statements:

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P271: Use in well ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P311: If swallowed: Calla Poison Center or physician.

EU Hazard Classificaton per Directive 1999/45/EC:

Classificaton: [F] Flammable, [Xn] Harmful

Risk Phrases: R10: Flammable, R36/38: Irritating to eyes and respiratory system, R45: May cause cancer, R46: May can

heritable genetic damge, R65: Harmful: may cause lung damage if swallowed.

Safety Phrases: S7/9: Keep container closed and in a well ventilated space, S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice, S39: Wear eye/face protecton.

Annex II Hazard Symbol:



Hazards not otherwise classified: None

GruberCare Interphase Wax Section 3 – Composition/Information on Ingredients

	1 6				
Chemical Name	CAS#	EINECS#	Weight %		
Mineral Spirits	64742-88-7	265-191-7	60-70%		
Solvent Naptha Light	64742-95-6	265-199-0	20-30%		
Aromatic					
Blend of Paraffin waxes	8002-74-2	232-315-6	1-10%		
and Hydrocarbon waxes					

Each of the other components is present in less than 1 percent concentration (0.1% concentration) for potential carcinogens, reproductive toxins, respiratory tract sensitizer, and mutgens.

Section 4 - First Aid Measures

Description of necessary measures, subdivided according to the different routes of exposure:

Inhalation: Remove to fresh air. In the event of breathing difficulties, get medical advice/attention immediately.

Eve Contact: Flush eyes under gentle running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Continue flushing for a minimum of 15 minutes. Remove contact lenses, if worn. Seek medical attention.

Skin Contact: Remove contaminated clothing. Wash skin thoroughly with plenty of soap and water. Consult a physician if irritation develops and persists. Wash contaminated clothing before using it again.

Ingestion: Call a physician or poison control center. Take a copy of the label and SDS with the victim to the health professional.

Most important symptoms/effects, acute and delayed: Persons with pre-existing skin disorders, eye problems, impaired respiratory function may be more susceptible to the effects of the substance.

Indication of immediate medical attention and special treatment needed: Treat symptoms and eliminate overexposure.

Section 5 - Fire-Fighting Measures

Suitable Extinguishing Media: Dry chemical, foam, carbon dioxide

Unsuitable Extinguishing Media: None known.

Unusual Fire or Explosion Hazards: Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Explosion Sensitivity to Mechanical Impact: Not Sensitive

Explosion Sensitivity to Static Discharge: Sensitive

Fire-Fighting Instructions: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus (SCBA) and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures: Remove all unnecessary personnel. Eliminate all sources of ignition. Wear appropriate protective equipment, including respiratory protection, as conditions warrant. Environmental precautions: Prevent spilled material from entering sewers, storm drains, or other unauthorized treatment drainage systems, and natural waterways. Notify fire authorities and appropriate federal, state, and local agencies.

Methods and materials for containment and cleaning up:

Small spills: Absorb spill with inert material (e.g. vermiculite, sand, or earth), then place in suitable container. Large spills: Eliminate all ignition sources; ground all equipment; do not walk through spill; stop spill if possible; prevent entry into sewers, confined spaces, etc; use a vapor suppressing foam to reduce vapors; absorb spill with noncombustible matter and transfer to containers; use non-sparking tools to collect absorbed material. Dispose of in accordance with applicable Federal, State, and local regulatory procedures.

Section 7 - Handling and Storage

Precautions for safe handling: Do not eat, drink, or smoke during use. Wash thoroughly after handling. Conditions for safe storage, including any incompatibilities: Store in a dry, cool, well-ventilated place, keep away from possible sources of ignition. Flammable material-keep away from heat, sparks, and flame; sudden releases of hot organic vapors or mists from process equipment operating at elevated temperature may result in ignitions without the presence of obvious ignition sources.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Protective Clothing/Equipment:

Hand protection: Compatible protective gloves recommended. Wash hands after removing gloves. If necessary, refer to US OSHA 29CFR1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australia, or Japan. Body protection: Use body protection appropriate for the task. Coveralls, rubber aprons, or chemical protective clothing made from natural rubber are generally acceptable, depending upon the task. If necessary, refer to appropriate Standards of Canada, EU, Australia, and Japan. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection as described in US OSHA 29CFR1910.136.

Eye protection: Splash goggles or safety glasses with side shields recommended to prevent eye contact. If necessary refer to US OSHA 29CFR1910.133, Canadian Standards, and European Standard EN166, Australian Standards, or relevant Japanese Standards.

Respiratory protection: Not normally required when working with this product. If exposure limits are exceeded, use only respiratory protection authorized in the US Federal OSHA Respiratory Protection Standard (29CFR1910.134), equivalent US State Standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

	OSHA PEL		ACGIH TLV	
Ingredient	TWA	STEL	TWA	STEL
Mineral Spirits	100 ppm	None established	100 ppm	None established
Solvent Naptha Light Aromatic	100 ppm	None established	100 ppm	None established
Blend of paraffin waxes and hydrocarbon waxes	None established	None established	None established	None established

Section 9 - Physical and Chemical Properties

Appearance: yellow liquid wax Odor: slight hydrocarbon odor Odor Threshold: not available

pH: not available

Freezing/Melting Point: not available **Boiling Point:** 313-395°F (156.11-201.67°C)

Flash Point: >112°F (>44.44°C) Flash Point Method: not available

Evaporation Rate: 0.6 **Flammability:** Flammable

Upper/lower flammability or explosive limits: not

available

Vapor Pressure: 0.71 kPa Vapor Density (Air=1): 4.4 Relative Density: 0.79 Water Solubility: insoluble Other Solubilities: not available

Partition coefficient: n-octanol/water; not available

Auto-ignition Temperature: not established **Decomposition Temperature:** not available

Viscosity: not applicable

Calculated VOC: 5.87 lbs/gal (704.5 g/l)

Section 10 - Stability and Reactivity

Reactivity: None known.

Chemical Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Possibility of hazardous reactions: Will not occur

Conditions to Avoid: Excessive heat, open flame, and other sources of ignition, incompatible materials.

Incompatible materials: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition may produce oxides of carbon and other toxic gases.

Section 11- Toxicological Information

Information on the likely routes of exposure: Skin, Eye, Inhalation, and Ingestion. **Symptoms related to the physical, chemical, and toxicological characteristics:**

Eye: Contact with liquid or vapor can cause irritation.

Skin: Repeated or prolonged exposure may cause skin irritation with dryness and cracking.

Ingestion: May cause gastrointestinal irritation with headache, nausea, vomiting, dizziness or drowsiness. Aspiration hazard if swallowed and enters airways.

Inhalation: Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation.

Delayed and immediate effects and also chronic effects from short and long-term exposure: See above.

Numerical measures of toxicity: Not available.

Carcinogenicity: Neither this product nor any of its components are considered carcinogenic by OSHA, IARC, NTP, or

ACGIH.

Irritancy of product: None known. **Sensitization to the product:** None known.

Reproductive toxicity:

Mutagenicity: No mutagenic effects in humans. Embryotoxicity: No embryotoxic effects in humans. Teratogenicity: No teratogenic effects in humans.

Reproductive toxicity: No reproductive effects in humans.

Section 12 - Ecological Information

Eco-toxicity: No data available

Persistence and degradability: no data available. **Bio-accumulative potential:** information not available

Mobility in soil: information not available **Other adverse effects:** None known.

Section 13 - Disposal Considerations

Disposal: Follow applicable Federal, state, and local regulations.

EU Waste Code: Not listed.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101):

NOTE: This product may be shipped as a "Limited Qty": For Flammable liquids in Packing Group III, inner packagins of 10.0L or less can be classified as a "Limited Qty."

Road and Rail Transport: UN Number: UN1268

UN proper shipping name: Petroleum Distillates, n.o.s.

Transport hazard classes: Class 3 Flammable

Packaging group: PGIII

Environmental hazards: Not designated to be Marine Pollutants (49CFR172.101, Appendix B)

Special precautions for user: None

North American Emergency Response Guidebook: 128

RQ Quantity: None

International Air Transport Association (IATA): This product is considered as dangerous goods. This product may be shipped via air in max container size of 5L. Maximum net qty. per package-60L passenger aircraft and 220L cargo aircraft.

International Maritime Organization (IMO): This product is considered as dangerous goods.

European Agreement Concerning the International Carriage of Dangerous Goods by Road (ADR): This product is considered by the United Nations Economic Commission for Europe to be dangerous goods.

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261.??): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) not listed

SARA Toxic Chemical Section 313(40 CFR 372.65): Not listed

SARA EHS Section 302(Extremely Hazardous Substance) (40 CFR 355): Not listed

SARA Hazardous Chemical Section 311/312: Acute Health: Yes, Chronic Health: No, Fire: Yes, Reactivity: No

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed OSHA Specifically Regulated Substance (29CFR 1910.????)

California Proposition 65: This product may contain ingredients in trace amounts that are currently listed on California Proposition 65 Chemical List. WARNING! This product may contain trace ingredients that are known to the State of California to cause cancer or reproductive harm.

HMIS: Health: 2 Flammability: 2 Reactivity: 0 NFPA: Health: 1 Flammability: 2 Reactivity: 0

Inventory Lists: This product or its components are listed on the following inventory lists:

TSCA	Australia AICS	Canada DSL	China IECSC	Europe EINECS	Japan ENCS	Korea ECL	New Zealand NZIoC	Taiwan
Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed

Asia- Pac	F F	
Listed	Listed	Listed

Canadian Environmental Protection Act (CEPA) priorities substances lists: No component of this product in on the CEPA First Priorities Substances Lists.

Canadian WHMIS Classification and Symbols: This product is categorized as Class B Division 4 Flammable solid and D2B Materials having other toxic effects as per the Controlled Product Regulations.



EU Hazard Information: See Section 2.

Australia Standard for the Uniform Scheduling of Drugs and Poisons: Not applicable.

Japan: The components of this product are not listed as Class I specified chemical substances, Class II specified chemical substances, or designated chemical substances by the Japanese MITI.

Section 16 - Other Information

Prepared By: Stephanie Nichols **Revision Notes:** updated to SDS format

Product Grades Available from the R. J. Marshall Company (this list may be incomplete):

010621	010622	010623	010624	010651

Disclaimer: Information contained herein is presented in good faith and is based on data believed to be accurate. However no warranty is expressed or implied regarding this information or the results obtained from the use of this Safety Data Sheet, whether it originates with The R. J. Marshall Company or others. This Safety Data Sheet relates only to the specific material designated herein. It does not relate to use with other material or processes. This information is supplied with the condition that the use will make appropriate determination as to its suitability for their purpose prior to using it.