

C-TEC™ CT-FR Z30S & INT3

Typical Physical Properties

| | |
|------------------------------|--------------------|
| Color | white to off-white |
| Mean Particle Size (microns) | 2-3 |
| 99% Less Than (microns) | 25 |
| Decomposition Temp. (°F) | >550 |

C-TEC™ CT-FR series flame retardants and smoke suppressants for polymers are ultra fine white powders of inorganic complexes.

| C-TEC FR PRODUCTS | Z30S | INT3 |
|-------------------|------|------|
| Specific Gravity | 4.5 | 4.5 |

Potential Antimony Oxide replacements.

APPLICATIONS: **C-TEC CT-FR** additives are designed to help the formulator achieve high levels of flame retardancy with reduced levels of smoke in halogenated and other polymers. They are particularly effective in PVC based wire & cable, sheet and film, and coatings.

C-TEC CT-FR INT 3 is designed to help the formulator achieve high levels of flame retardancy and antimony trioxide replacement in halogenated polymers including PVC. CT-FR INT 3 also reduces smoke emissions compared with antimony trioxide and may provide lower and more consistent tinting strength than some commercial grades of antimony trioxide.

HEALTH AND SAFETY: Refer to the Material Safety Data Sheet

PACKAGING: 50 lb. bags, pallet weight 2000-3000 lbs.

Terms and Conditions of Sale: All statements, technical information and recommendations are based on tests we believe to be reliable, the accuracy or completeness is not guaranteed, and the following is made in place of all warranties, expressed or implied. Our only obligation is to replace product proved to be defective. We shall not be liable for any injury, loss or damage, direct or indirect, from using or not being able to use the product. Before using, customer must determine the suitability of the product for the intended use and customer assumes the responsibility. This statement may not be changed except by an agreement signed by an officer of The R.J. Marshall Company.

August 2015