

PE 2000

Typical Properties

Specific Gravity	0.96
Fiber length (mm):	1 - 3
Fiber diameter (um):	1.4
Free Moisture:	<5%
Bulk Density (lbs/gal)	0.2
Bulk Density (lbs/ft ³)	1.6
Polyethylene Pulp (%)	100

PE 2000 is a white, 100% expanded, Polyethylene Pulp. It is the most functional PE, the most economical and versatile PE to use.

Advantages:

- * Designed to rapidly disperse with high or low shear into either water or solvent borne systems.
- * Very inert making it highly resistant to alcohols, acids, alkalis, esters, aliphatic and aromatic hydrocarbons.
- * Resistant to harsh detergents, gasoline, oils, brake, and transmission fluids.

APPLICATIONS: Designed for use as a medium fiber in elastomeric, vinyl and asphaltic roof coatings and mastics, caulks, exterior and interior plasters and stuccos, and joint cements.

HEALTH AND SAFETY: Refer to the Safety Data Sheet

PACKAGING: 15lb bag, 2000lb pallet

Terms and Conditions of Sale: All statements, technical information and recommendations are based on tests we believe to be reliable, the accuracy or completeness is not guaranteed, and the following is made in place of all warranties, expressed or implied. Our only obligation is to replace product proved to be defective. We shall not be liable for any injury, loss or damage, direct or indirect, from using or not being able to use the product. Before using, customer must determine the suitability of the product for the intended use and customer assumes the responsibility. This statement may not be changed except by an agreement signed by an officer of The R.J. Marshall Company.

December 2016