



Polyethylene Pulp

Polyethylene pulp is characterized as an excellent thixotrope and thickener with relatively low resin demand and a high degree of resistance to water, acids, alkalis, detergents, aliphatic and aromatic hydrocarbons, esters and ketones. The principle advantage of polyethylene pulp is that you can take advantage of synergistic effects of several materials that can't be achieved with simple blending. Polyethylene pulp is designed to meet the specific requirements of the user (i.e. fiber length, density, thixotrophy in solvents, in water, plus 100% solids systems). All Polyethylenes are designed to give you the greatest dispersability. The standard pulps give you a choice of density, fiber length, and thixotrophy needed for your system. In addition to the standard products, specialty products can be provided with your choice of specific gravity and thixotrophy.

Code	Description	Typical Uses*	Fiber Length (mm)	Fiber Diameter (microns)	Specific Gravity (water=1)	Density lbs/ft ³	Density lbs/gal	Fiber Profile
24JA	100% polyethylene pulp	A,B	0.1	10	0.91	56.8	7.6	Med
26JA	100% polyethylene pulp	A,C	0.8 - 1.1	10	0.91	56.8	7.6	High

Use Codes:

A= Caulks, B= Spray & Paint Coatings, C= Brush or Trowel Paints,

Marshall Additive Technologies assumes no responsibility for the result of any application made of any information contained on this technical data sheet, nor does MAT assume any liability for infringement of any patent that may result from the application of such information.

"We Seek to Make Our Customer Successful"

October 2017