Safety Data Sheet

Spravlite 100 Series

MSDS No. 9780.13

Date of Preparation: 7/16/96	0					
So	ation 1 Chamical Dr.	aduat and Ca	mony Idon	ficition	Revis	HMIS
Product/Chemical Name General Use: Filler or exte Manufacturer: The R. J. 26776 W. Southfield	ender	Emerge Date Re Prepare	ency Phone: (800 evised: 9/14/18 er: Stephanie Nich) 424-9300		H 1 F 0 R 0 PPE ^{\dagger} E ^{\dagger} Sec. 8
1 1010. (2	· · · ·	Tazards Identi	ification			
Classification of the chen	nical in accordance with parag			d		
Do not handle unti Wear protective glu If exposed or conce Store locked up.		ction. tion.	od.			
	is in accordance with local legal	ations.				
Hazards not otherwise cla	-	ations.				
	-		on on Ingree	dients		
	assified: none Section 3 - Compositio Ingredient Name	on / Informati CAS Number	Percentage	dients		
	assified: none Section 3 - Compositio	on / Informati	U	dients		
	assified: none Section 3 - Composition Ingredient Name Crystalline Silica Calcium Carbonate	on / Informati CAS Number 14808-60-7	Percentage1% max100% max	dients		
Description of the necessa Inhalation: If over Eye Contact: Flux Skin Contact: Wa Ingestion: Drink p	assified: none Section 3 - Composition Ingredient Name Crystalline Silica Calcium Carbonate	On / Informati CAS Number 14808-60-7 1317-65-3 First Aid Mean ording to the different ns, remove to a vent aking care to rinse un d water. e of very low toxicit	Percentage 1% max 100% max asures ent routes of expo ilated area. nder eyelids. Do r y.	sure:		
Description of the necessa Inhalation: If over Eye Contact: Flux Skin Contact: Wa Ingestion: Drink p Most important sympton	assified: none Section 3 - Composition Ingredient Name Crystalline Silica Calcium Carbonate Section 4 - ary measures, subdivided acco rcome by high dust concentration sh eyes thoroughly with water ta ash skin thoroughly with soap an olenty of water. Considered to b	CAS Number 14808-60-7 1317-65-3 First Aid Me ording to the difference ns, remove to a ventaking care to rinse und water. e of very low toxicit May cause dryness of	Percentage 1% max 100% max asures ent routes of expo ilated area. nder eyelids. Do r y. of skin, eye irritation	sure:		
Description of the necessa Inhalation: If over Eye Contact: Flux Skin Contact: Wa Ingestion: Drink p Most important sympton	assified: none Section 3 - Composition Ingredient Name Crystalline Silica Calcium Carbonate Section 4 - ary measures, subdivided accor rcome by high dust concentration sh eyes thoroughly with water ta ush skin thoroughly with soap and olenty of water. Considered to b ms/effects, acute and delayed: I medical attention and special t	CAS Number 14808-60-7 1317-65-3 First Aid Me ording to the difference ns, remove to a ventaking care to rinse und water. e of very low toxicit May cause dryness of	Percentage 1% max 100% max asures ent routes of expo ilated area. nder eyelids. Do r y. of skin, eye irritation None known.	sure:		

Spraylite 100 Series

Section 6 - Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures: Avoid dust formation. Spilled materials may cause slippery conditions when wet.

Methods and materials for containment and cleaning up: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Section 7 - Handling and Storage

Precautions for safe handling: Avoid generating dust during handling. If excessive dust is generated, provide adequate ventilation and use proper respiratory and personal protective equipment.

Storage Requirements: Keep container tightly closed in a dry and well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

Protective Clothing/Equipment: Wear suitable protective clothing, gloves, and safety glasses.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

	OSHA PEL		ACGIH TLV	
Ingredient	TWA	STEL	TWA	STEL
Particulates not otherwise classified	15 mg/m ³ total 5 mg/m ³ respirable	None established	None established	None established
Crystalline Silica	$\frac{30 \text{ mg/m}^3}{(\% \text{ SiO}_2 + 2) \text{ total dust}}$ $\frac{10 \text{ mg/m}^3}{(\% \text{ SiO}_2 + 2) \text{ respirable dust}}$	None established	0.025 mg/m ³ respirable dust	None established

Section 9 - Physical and Chemical Properties

Appearance: off-white powder	Vapor Pressure: not applicable
Odor: odorless	Vapor Density (Air=1): not applicable
Odor Threshold: not applicable	Relative Density: varies
pH: not applicable	Water Solubility: Slight
Freezing/Melting Point: not applicable	Other Solubilities: n/a
Boiling Point: not applicable	Partition coefficient: n-octanol/water; not applicable
Evaporation Rate: not applicable	Auto-ignition Temperature: not applicable
Flash Point: not applicable	Decomposition Temperature: >800°C (>1472°F)
Flash Point Method: not applicable	Viscosity: not applicable
Flammability Classification: Non-flammable.	
Upper/lower flammability or explosive limits: not	
applicable	

Section 10 - Stability and Reactivity

Reactivity: This product is stable at room temperature in closed containers under normal storage and handling conditions.
Chemical Stability: No decomposition if stored as directed.
Possibility of hazardous reactions: Reacts with acids to form carbon dioxide.
Conditions to Avoid: Temperatures above 40°C (104°F).
Incompatible materials: Acids.
Hazardous Decomposition Products: Carbon dioxide

Spraylite 100 Series

Section 11- Toxicological Information

Information on the likely routes of exposure: Eye, Skin, Inhalation.

Symptoms related to the physical, chemical, and toxicological characteristics:

Eye: Nuisance dust. May cause irritation through mechanical abrasion.

Skin: Nuisance dust. May cause irritation through mechanical abrasion.

Inhalation: Nuisance dust. Overexposure to dust may cause irritation to the respiratory tract. Ingestion: Unlikely.

Delayed and immediate effects and also chronic effects from short- and long-term exposure: Long term exposure to crystalline silica can cause lung injury (silicosis). IARC and NTP have determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure.

Numerical measures of toxicity:

Acute Oral Toxicity: LD50 (oral): >5000 mg/kg

Carcinogenicity: IARC and NTP consider crystalline silica to be a known human carcinogen. IARC-Group 1.

Section 12 - Ecological Information

Eco-toxicity: Fish; >5000 mg/l Persistence and degradability: Not applicable Bio-accumulative potential: not applicable Mobility in soil: Not applicable Results of PBT and vPvB assessment: Non-classified PBT or vPvB substance.

Section 13 - Disposal Considerations

Disposal: Recycle or landfill if possible. This substance is inert and does not require special disposal methods. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101): This product is not classified as dangerous under the transport regulations for road, rail, sea, or air transport.

UN Number: not classified as dangerous goods UN proper shipping name: not classified as dangerous goods Transport hazard classes: None Packaging group: None Environmental hazards: None Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: No hazardous goods. Special precautions for user: None

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33) RCRA Hazardous Waste Classification (40 CFR 261.??): Not classified CERCLA Hazardous Substance (40 CFR 302.4) Not listed SARA Toxic Chemical Section 313: Not listed SARA EHS (Extremely Hazardous Substance) Section 304: Not listed SARA 311/312 Hazards: Acute/Chronic Health Hazard

Prop65: This product can expose you to chemicals including crystalline silica which is known to the State of California to cause cancer.

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

Inventories:

TSCA	Australia AICS	Canada DSL	China IECSC	Europe EINECS	Japan ENCS	Korea ECL
Listed	Listed	Listed	Listed	Listed	Listed	Listed

New Zealand	Philippines	Taiwan
NZIoC	PICCS	NECI
Listed	Listed	Listed

Section 16 - Other Information

Prepared By: Stephanie Nichols **Revision Notes:** updated 9/14/18

Product Grades Available from the R. J. Marshall Company (this list may be incomplete):

Spraylite 101	Spraylite 131
Spraylite 110	Spraylite 132
Spraylite 110A	Spraylite 133
Spraylite 110V	
Spraylite 120	
Spraylite 121	
Spraylite 130	

Disclaimer: Information contained herein is presented in good faith and is based on data believed to be accurate. However no warranty is expressed or implied regarding this information or the results obtained from the use of this Safety Data Sheet, whether it originates with The R. J. Marshall Company or others. This Safety Data Sheet relates only to the specific material designated herein. It does not relate to use with other material or processes. This information is supplied with the condition that the user will make appropriate determination as to its suitability for their purpose prior to using it.