

26776 W. 12 Mile Road Southfield, MI 48034 248-353-4100 phone 248-948-6460 fax 800-338-7900 toll free 888-514-8600 customer care www.Rjmarshall.com

PE210, PE230, PE250, PE270, PE290 Polyethylene Pulp

Typical Characteristics and Properties

Specific Gravity	2.8	
Fiber length (mm)	0.1	
Fiber diameter (um)	5	
Free Moisture:	<2.5%	

PE230 PE250 PE270 PE210 Bulk Density (lbs/gal) 4.09 3.42 2.1 1.8 1.3 Bulk Density (lbs/ft3) 30.6 25.6 17 14.7 10.4 Polyethylene Pulp (%) 5 7 9 3 Talc (%) 99 97 95 93 91 PE products are low cost, white, expanded, highly fibrillated polyethylene pulp with an average BET surface area of 8.45 m2/g giving it a great deal of reinforcing functionality.

Advantages:

- * Designed to rapidly disperse into any low or high sheer system.
- * Very inert making it highly resistant to alcohols, acids, alkalis, esters, aliphatic and aromatic hydrocarbons.
- * Resistant to harsh detergents, gasoline, oils, brake, and transmission fluids.

APPLICATIONS: Designed for use as a fiber filler in elastomeric roof coatings, stuccos, caulks, cements, crack fillers, exterior and interior plasters, and joint cements. Recommended starting use level is 10% and adjusting to degree of fibrillation desired and degree of economical fibrous filler.

HEALTH AND SAFETY: Refer to the Safety Data Sheet

PACKAGING: 50lb bag, 2000lb pallet

November 2020